



**2-Strand Rope Fence**

**NOTES:**

1. POSTS TO BE EITHER HARDWOOD STAKES OR METAL T-POSTS SIX FEET (6') LONG MINIMUM WITH A MINIMUM EMBEDMENT OF 2-FEET INTO THE GROUND.
2. ROPE TO BE ATTACHED TO FENCE POSTS USING PLASTIC OR WIRE TIES.
3. WARNING SIGN SHALL BE MADE OF DURABLE, WEATHERPROOF MATERIAL. LETTERING TO BE TIMES NEW ROMAN OR AERIAL FONT, RED IN COLOR, MINIMUM OF 1" IN HEIGHT, SECURELY ATTACHED IN THE UPPER HALF OF THE FENCE, AND PLACED AT 50-FOOT MAXIMUM INTERVALS.
4. FLAGGING TAPE SHALL BE 1-3/16 INCH, 4-MIL THICKNESS, NO-ADHESIVE VINYL, FLUORESCENT SOLID COLOR, AND ATTACHED TO THE TOP ROPE ON BOTH SIDES OF THE WARNING SIGN.
5. CONSTRUCTION FENCE (PC STD DTL 121) MAY BE USED IN LIEU OF PRESERVATION WHEN DIRECTED BY THE ENGINEER OR SPECIFIED ON THE PROJECT PLANS.

<i>ISSUED:</i>		<b>STANDARD DETAIL</b>		<b>DETAIL NO.</b>
12/16		Preservation Fence (Type A)		120
<i>REVISED:</i>				SHEET 1 of 1